

UT Series Modulated Red Laser Module

Part No: UT5-7G-650




Product Features

- TTL Modulation from CW up to 155 MHz
- Collimated or Adjustable focus beam
- Custom Options Available

Application

- Measurement
- Bioanalytical
- Automation
- Alignment

Mechanical Drawing



Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage.

Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.

Specification

OPTICAL

| | |
|-------------------------------|-------------------------------|
| Wavelength | 650 nm |
| Optical Output Power | 7 mW |
| Stability | <1% |
| Wavelength Drift | 0.2 nm/°C |
| Noise (20MHz Bandwidth) | <0.5% RMS |
| Laser Class | Class IIIb |
| Laser Operation ¹ | Continuous |
| Laser Structure | Single Mode Laser |
| Divergence at the collimation | <0.5 milliradian |
| Spot Size | Adjustable or collimated(5mm) |
| Minimum Spot Size | <60 μm at <10" distance |
| Bore sight Accuracy | <2.5 mm/m |
| Pointing Stability | <50 μrad |

ELECTRICAL

| | |
|------------------------|------------------------------|
| Operating Voltage | 3.5 to 5 VDC |
| Operating Current | < 120 mA |
| Modulation | 0 Hz to 155 MHz |
| TTL Input | Low (0~0.8 V), High (3~5 V) |
| Electrical Connections | +(Red), -(Black), TTL(White) |

MECHANICAL

| | |
|-------------------------------------|------------------------------|
| Dimension | 12 mm(D)x 51mm (L) |
| Cable | 200 mm |
| Operating Temperature | -10°C to +50°C |
| Storage Temperature | -40°C to +80°C |
| Heat Sink Requirements ² | Recommended for extended use |

Notes

1. For CW Operation: Connect the white wire to the red wire.
2. Heat Sink: The UT Series Red Laser Diode Module is designed to dissipate heat through its body. Do not use a thermally insulating material for mounting. Do not restrict air circulation around the device. An additional heat sink can be used to maximize the performance and life time of the laser

Caution: The case is internally connected to the circuit; damage to the anodized surface may result in failure of the laser module.




UT5-7G-650 is sold only for use in OEM equipment. The OEM is responsible for compliance with all applicable safety regulations

UT Series Modulated Red Laser Module

Part No: UT5-7G-650

TTL Modulation

The UT series red laser module is TTL modulatable between 0 and the full power by applying an external TTL input signal (e.g. from function generator) using third white wire. When the TTL input is Low the laser power is completely off. When the TTL input is high the laser output is at Full Power. The TTL signal can be any on-off time combination.



Continuous Operation

The UT series laser module can be operated continuously by applying a high signal to the TTL input which can be done by connecting the white wire and red wire together.

