

# TECGL-520-USB

## Thermo-Electrically Cooled Green Lasers



### Specifications

#### OPTICAL

Wavelength	520 nm
Optical Output Power	5-100 mW
Laser Power Stability	< 0.5%
Laser Structure	Single Mode
Laser RMS Noise	< 0.5%
Polarization Ratio	> 20:1 (higher ratio available on request)
Beam Size	3 mm (collimated)
Divergence (full)	< 0.5mrad
Beam Pointing Stability	< ± 10 μrad
Warm-Up time	< 1 min

#### ELECTRICAL

Operating Voltage	3.3 V DC
Operating Current	< 1 A

#### MECHANICAL/ENVIRONMENTAL

Dimension	1" ( Dia ) x 3" ( L )
Operating Temperature	+10°C to +40°C
Storage Temperature	-40°C to +80°C
Heat Sink Requirements	Recommended for extended use

### TECGL-Series Laser Product Features

- Integrated TEC and Laser Controller
- RS-232/USB Interface
- Excellent Power & Wavelength Stability
- Compact Size
- Long Life-Time & Low Power Consumption

### TECGL-Series Laser Applications

- Bioanalytical
- Measurement
- Confocal Microscopy

**TECGL-Series** Thermo-Electrically Cooled Green Laser is a compact self-contained, highly reliable laser operating at very stable wavelength and power. The build-in temperature controller stabilizes the laser temperature within ±0.01°C. The laser output power stability is better than 1% over long term. Extremely stable power, low noise and excellent beam pointing stability of this laser makes it ideal for bioanalytical, measurement and imaging applications. It is powered by a wall mount power adaptor (supplied with the laser) for plug & play operation.

**TECGL-Series** lasers can be customized to include beam shaping optics and modulation.

**Operational Hazard-Semiconductor Laser Diode Module:** This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage.

**Limited Warranty:** One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.

**World Star Tech**

[sales@worldstartech.com](mailto:sales@worldstartech.com)

321 Lesmill Rd. Toronto, ON, M3B 2V1 Canada


[www.worldstartech.com](http://www.worldstartech.com)

[info@worldstartech.com](mailto:info@worldstartech.com)

Tel: (416) 363-3332 Fax: (416) 363-3112

# TECGL-520-USB

## Thermo-Electrically Cooled Green Laser Modules :Mechanical Dimensions



## TECGL-Series Laser Ordering Information

Part# TECGL-pppG(c)-λλλ-USB

Option	Meaning	Values
<b>ppp</b>	Laser output power (mW)	5, 10, 20, 30, 50, 100
<b>(c)</b>	Circular laser diode beam (optional)	C (max power 60 mW with circular beam)
<b>λλλ</b>	Wavelength (nm)	520 +/-5 nm
<b>TTL</b>	TTL Modulation (external)	Max 1MHz (upto 30 mW). Higher power 3KHz

Example Part Number :**TECGL-5GC-520-USB** (5mW, 520 nm, circular beam )



Class IIIB Modules sold solely for use in OEM equipment; OEM is responsible for compliance with all safety regulations.

**World Star Tech**

[sales@worldstartech.com](mailto:sales@worldstartech.com)

321 Lesmill Rd. Toronto, ON, M3B 2V1 Canada

[www.worldstartech.com](http://www.worldstartech.com)

[info@worldstartech.com](mailto:info@worldstartech.com)

Tel: (416) 363-3332 Fax: (416) 363-3112